

**CAUTION** Keep out of reach of children  
Read safety directions before using

CYNDAN MOLY PLUS forms a thin, dry black protective film that adheres to surfaces for long lasting lubrication under extreme pressure and high temperatures. CYNDAN MOLY PLUS protects surfaces from corrosion, moisture and rust and resists abrasives, dust and sand.

- Withstands most acids, alkalis, oils and water.
- Preserves friction points.
- Reduces sticking problems.
- Effective for temperatures up to 315°C.

Typical applications include: road sweeping vehicles, lawn care machinery, playground equipment, piping fixtures and threads, door lock lubrication, lubrication of door hinges and sliding gates, dampers on air conditioning equipment, motor cycle shops, bicycle repairs, bowling alley, equipment such as, pin ring pulleys, sweeper arms and distributors gears. Marine mechanics use 'Cyndan Moly Plus' for carburettor linkages, shift linkages, clamp screws, pivot shafts, compression release linkages, slip way cables and wire ropes. Curtain sided trucks, forklift lifting chains, tanning drums and timber milling equipment.

All chain driven equipment, plant or machinery can be dry lubricated with 'Moly Plus'. Results of this dry lubrication is that contamination in the work place is not transferred to the drive chain. This normal transfer of contaminates mixes with the lubrication grease producing a grinding paste, which causes mechanical problems. This abrasive wear is avoided by the use of dry lubrication with 'Cyndan Moly Plus'.

**DIRECTIONS FOR USE:**

SHAKE WELL BEFORE USING

For best results, CYNDAN MOLY PLUS should be applied to a clean dry surface. Hold can upside down and shake until metal ball moves freely. Shake for up to 30 seconds.

Hold can 20 - 25 cm from surface and spray in a thin, even film. Avoid excessive spraying as this diminishes efficiency of MOLY PLUS.

After use invert can and press button once or twice to clear nozzle. Allow coated object to air dry to touch before using.

**SAFETY & FIRST AID:**

**WARNING:** Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

**CAUTION: HIGHLY FLAMMABLE**

Contents under pressure. DO NOT spray near fire or open flame. DO NOT puncture or incinerate can. Avoid prolonged exposure to sunlight. DO NOT store at temperatures over 50°C. Use with adequate ventilation. Avoid prolonged breathing of vapour or repeated contact with skin.



1/7 Jubilee Avenue Warriewood NSW 2102 AUSTRALIA  
ph +61 2 9998 5688 www.cyndan.com.au

CYNDAN™

# Moly-Plus

## DRY "MOLY" LUBRICANT

Contains Micron-sized  
Molybdenum disulphide

WITHSTANDS  
EXTREME TEMPERATURES  
AND HEAVY PRESSURES

### 350g Nett



UN 1950  
AEROSOLS  
HAZCHEM 2Y  
CLASS 2

PROPELLANT:  
HYDROCARBON

PRODUCT OF  
AUSTRALIA



CYNDAN  
chemical solutions